

2Amp regulated 24V AC power supply unit



features

- ✓ linear power supply
- ✓ operational input voltage 100V to 240V ac
- ✓ long power leads, 1.8 metres each
- ✓ integral mounting lugs
- ✓ indoor use only

technical data

| | |
|--------------------------------------|------------------------------------|
| Rated Input Voltage | Nominal 230V AC |
| Output Voltage | AC24V |
| Maximum Load Current | 2.0A |
| Frequency Rated | 50Hz |
| Load Regulation | ± 10% |
| Insulation Resistance | 100MΩ @ DC500V |
| Dielectric Strength, Primary to Core | AC4200 V 1 Minute |
| Dielectric Strength, Sec. to Core | AC2100 V 1 Minute |
| Safety Approvals | CE |
| Dimensions | 96.8mm (l) x 68.5mm (w) x 72mm (h) |
| Weight | 1.1Kg |
| Mean Time Between Failure | 40,000 Hours |
| Operating Temperature | 0° C ~ +40° C |
| Operating Humidity | 20% ~ 80% RH |

Genie CCTV Limited

Unit D city park, 26 watchmead, welwyn garden city, herts AL7 1LT
 tel: +44(0) 1707 330541 fax +44(0) 1707 330543
 website: geniecctv.com email: info@geniecctv.com