

# ZM-CR SERIES

## Colour Series of CRT Monitors



The ZM-CR series of monitors have been designed to provide both high quality images and be highly reliable and robust monitor. The monitor comes in 3 sizes 14", 15" and 21", the 15" model is high resolution, 800TVL.

All the monitors have a robust metal casing, and come with the additional feature of carry handles to make the installation process easier.

All the monitors in the range work with both PAL and NTSC signals and in a voltage range of 100 – 240 Vac allowing the monitors to be used virtually all over the world.

### Ordering Information

ZM-CR114NP-II 14" Colour Monitor

ZM-CRH115NP-II 15" Colour Monitor, High Resolution

ZM-CR121NP-II 21" Colour Monitor

### Perfect Partners

Monitor Brackets



MISC (Ceiling mount)



MISW (Wall mount)

### KEY FEATURES:

- 14", 15" and 21" models
- PAL & NTSC compatible
- Auto loop through
- High Resolution (15" model)
- Multi-Language OSD set up
- Built-in microprocessor digital control
- Y/C input
- Dual Voltage 100-240 Vac

| MODEL                                 | ZM-CR114NP-II  | ZM-CR121NP-II  | ZM-CRH115NP-II   |
|---------------------------------------|--|--|------------------|
| CRT                                   | 14" Diagonal 90°   | 21" Diagonal 90°   | 15" Diagonal 90° |
| Video Signal                          | PAL/NTSC   |  |                  |
| Resolution                            | 400 TVL  | 580 TVL  | 800 TVL          |
| Audio In/Out                          | RCA in x 3 / RCA out x 3                                       |  |                  |
| Scanning Frequency                    | 15.625 KHz (PAL), 50Hz / 15.734KHz (NTSC) , 60Hz               |  |                  |
| Connector                             | Video BNC in x 1, Y/C in x 1<br>Video BNC out x 1, Y/C out x 1 | Video BNC in x 2, Y/C in x 1<br>Video BNC out x 2, Y/C out x 1 |                  |
| Power Requiements                     | 100-240Vac   |  |                  |
| Power Consumption                     | 65w  | 80w  | 95w              |
| Operating Conditions                  | Temperature: -10°C ~ +50°C, Humidity: 10% ~ 90%                |  |                  |
| External Dimensions in mm (W x H x D) | 350 x 350x 360   | 492 x 474 x 482  | 368 x 361 x 376  |
| Weight (approximate)                  | 14kg   | 27 kg  | 15 kg            |