

DVS



ADVANCED SECURITY PRODUCTS

DIGITAL RECORDERS

- 4 Channel 100fps Triplex Digital Video Recorder with audio
- Stable RTOS for stability and long term reliability
- Network capability using client software
- Motion detection, alarms and pre-alarm recording
- Extensive 'Go to' and search options



Entry Level DVR

TSDVR4E-250

This DVR is a smart and functional triplex digital recorder, ideal for domestic and small business CCTV systems. The unit offer four channels of recording at up to 100fps with adjustable levels of quality. Based on a Real Time Operating System (RTOS) platform for stability and long term reliability, the DVR is packed with many advanced features not normally found on such entry level products.

Four channels of audio recording, network capability, motion detection with pre-event recording and RS485 output for PTZ control are just some of the functions included in this model.

In addition it benefits from extensive search options and has an integrated data port for direct back-up to a USB stick or CD-RW. All programming features and operational functions are accessed from the intuitive Graphical User Interface menu system via the front panel buttons or infra red remote control. The DVR also offers the flexibility of connection to a VGA monitor.

\\ Additional features

- Port for back-up to USB stick or USB CDRW
- Intuitive Graphical User Interface
- Infra red remote control
- BNC or VGA output (switchable)
- Smart & attractive casing



Entry Level DVR

TSDVR4E-250

Specifications	
Video	
Input	4 composite BNC (NTSC/PAL) - 1.0Vp-p
Output (selectable)	1 composite BNC (NTSC/PAL) - 1.0Vp-p 1 VGA
Audio: Input & Output	4 Line In (RCA) 1 Line Out (RCA)
Alarm: Input & Output	4 1
OS	RTOS
Record	
Compression	MPEG-4
Video Format	PAL
Resolution	360 x 288, 720 x 576
Recording Speed	MAX. 100fps/4CH (352x288/CH) MAX. 25fps/4CH (720x576/CH)
Mode	Manual, Motion, Sensor and Schedule
Method	By Resolution, Frame rate & Quality
Multi Task: Triplex	Record, Playback & Transfer
Control Unit	IR Type Remote Control and Front keys
Serial Port	
Console	1 RS-232C
Camera Control	1 RS-485
Network	
Interface	ADSL, LAN
Dynamic IP	DDNS
Lan Port	10/100-base T Ethernet
Functions	Live, Search, P/T/Z/F, Backup
HDD: Capacity	1 IDE HDD
Back Up	
Network	Still Image & Video data
USB Stick/CDRW	Still Image & Video data
Electrical Specification	
Adaptor	Input: AC100-240V, 50/60Hz, 1.5A
Consumption	25W (approx)
Environmental Specification	
Temperature	50C ~ 400C
Humidity	30% ~ 90%
Size: Dimension	260(W) x 350(D) x 65 (H)mm

Due to our policy of continuous improvement the information supplied is subject to change without further notice

For further information please contact

